

CAMERIO

www.CAMERIO.com

Powerful Features with Simple Configurations



CAMERIO RN680 Series Digital Video Recorder

CAMERIO RN680 Series covers a full range of feature-rich and easy-to-use 4-, 8- and 16- channel digital video recorders. With the MPEG-4 compression and full-feature video recording, **CAMERIO** RN680 Series guarantees smooth and crystal clear video quality on both live monitoring and recording.

CAMERIO RN680 Series is designed to support up to 2 internal hard drives for enhancing the storage capacity and providing longer recording duration. Its built-in CD writer enables fast video footage extraction for evidential purpose.

CAMERIO RN680 Series equips with powerful features and easy-to-use operation, and is suitable for a wide range of applications from retail outlet, factory, property management and public utility installations.



Digital Video Recorder | RN680 Series



Features

- 4, 8 or 16 video & alarm input models
- Resolution up to 720x576 / 720x480 pixels
- Video compression: MPEG-4
- Recording rate up to 100/120fps
- Simultaneous recording, playback & network operation
- Main & call monitor outputs
- VGA output (optional)
- Support TCP/IP, DHCP & DDNS network
- Support up to 2 internal hard drives
- Built-in CD writer & USB interface for video extraction
- Schedule, alarm, motion detection & remote recording
- Fast & easy search for recorded video
- Accessible through web browser
- Telemetry control



Product Specifications

Model	RN684	RN688	RN6816
INPUT STANDARD	PAL/CCIR: 625 lines, 25 frames per second NTSC/EIA: 525 lines, 30 frames per second composite video, 1Vp-p, BNC, switchable		
INPUT CHANNELS	4	8	16
OUTPUT STANDARD	Main Monitor	BNC x 1, 1.0Vp-p, 75ohm	
	Call Monitor	-	BNC x 1, 1.0Vp-p, 75ohm
	VGA (Optional)	800x600, 1024x768, 1280x1024 pixels	
COMMUNICATION NETWORK	TCP/IP, DHCP, DDNS		
CONCURRENT USERS	2		
RECORDING MODE	Schedule / Motion / Alarm / Remote		
RECORDING RESOLUTION	D1 (PAL: 720x576 / NTSC: 720x480) Half D1 (PAL: 720x288 / NTSC: 720x240) CIF (PAL: 360x288 / NTSC: 360x240)		
HD TYPE	IDE interface, ATA66, 2 internal		
COMPRESSION FORMAT	MPEG-4, Advanced Simple Profile		
MAX. RECORDING RATE	PAL: 25fps (720x576); 100fps (360x288) NTSC: 30fps (720x480); 120fps (360x240)		
PLAYBACK SCHEDULE	Date, time, event		
PLAYBACK SPEED	1X, 2X, 4X, 8X, 16X, 32X		
ALARM IN/OUT	4 inputs, 1 output	8 inputs, 1 output	16 inputs, 1 output
AUDIO IN/OUT	2 inputs, 2 outputs		
BACKUP DEVICE	CD-RW, USB		
TELEMETRY STANDARD	RS-485, 1200, 2400, 4800, 9600, 19200bps		
TELEMETRY PROTOCOL	Pelco-P, Pelco-D, AD422, Fatrax 2		
VOLTAGE	External Adapter, AC 100~240V to DC 12V		
MAX. RATING	96W		
AMBIENT TEMPERATURE	0°C ~ 40°C		
RELATIVE HUMIDITY	30% ~ 90% (no condensation)		
DIMENSION	440mm (W) x 50mm(H) x 340mm(D)		
WEIGHT	4.9kg		

Recording Duration (Days) of CAMERIO RN688

D1 (720 x 576 pixels)		HD1 (720 x 288 pixels)		CIF (360 x 288 pixels)		- 8 cameras recording - HDD: 500GB - Moderate amount of motion - Best picture quality - Testing model: RN688
fps	Days	fps	Days	fps	Days	
25	12	50	7	100	9	
12	-	25	15	50	17	
8	29	8	36	8	54	

Remarks: Actual recording duration depends on actual camera situation.

PC Requirements

CPU : Pentium IV 2GB or above
RAM : 512MB or above
OS : MS Windows 2000, XP

CAMERIO

www.CAMERIO.com

TeleEye Group

Signal Communications Limited

Flat 202-3, 2/F, Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hong Kong
International: (852) 2995 5996 Hong Kong: (852) 2995 5992 Fax: (852) 2995 5901
Email: info@TeleEye.com Web: www.TeleEye.com

TeleEye Europe Ltd.
Tel: (44) 01628 776061
Fax: (44) 01628 407399
Email: ukinfo@TeleEye.com
Web: www.TeleEye.com

CAMERIO Japan, Inc.
Tel: (81) 42-742-2690
Fax: (81) 42-742-2616
Email: info@CAMERIO.co.jp
Web: www.CAMERIO.co.jp

TeleEye (Mauritius) Ltd.
Tel: (230) 686 5238
Fax: (230) 698 2179
Email: info@TeleEye.mu
Web: www.TeleEye.mu

TeleEye (S) Pte Ltd
Tel: (65) 67453921
Fax: (65) 67421965
Email: sales@TeleEye.com.sg
Web: www.TeleEye.com.sg

TeleEye Digital Technology (Shenzhen) Co., Ltd
Tel: (86) 755-2671-2122
Fax: (86) 755-2671-2287
Email: info@TeleEye.com.cn
Web: www.TeleEye.com.cn

TeleEye Philippines Inc
Tel: (63) 2 3650897
Fax: (63) 2 3651446
Email: contact@TeleEye.com.ph
Web: www.TeleEye.com.ph

TeleEye Hrvatska
Tel: (385) 52 383 101
Fax: (385) 52 383 101
Email: info@TeleEye.com.hr
Web: www.TeleEye.com.hr

TeleEye (South Africa) (Pty) Ltd
Tel: (27) 11 557 9200
Fax: (27) 11 706 3847
Email: info@TeleEye.co.za
Web: www.TeleEye.co.za