



Features

- Resolution: 480 TV lines
- Vari-focal f=9 ~ 22mm
- Auto Iris Lens
- 0.0 Lux (IR ON)
- Auto IR-cut Filter
- 40 IR LEDs / ~40m IR Range
- IP66 Weather Proof Standard

Specifications

| | | |
|-----------------------------------|---|--------------------------------|
| MODEL | SF489 | |
| PICK UP DEVICE | 1/3" Sony CCD | |
| TOTAL PIXELS | PAL: 752 (H) x 582 (V) | NTSC: 768 (H) x 494 (V) |
| HORIZONTAL RESOLUTION | 480 TVL | |
| LENS | 9 ~ 22mm (Aspherical IR lens) | |
| VIEW ANGLE (HORIZONTAL) | 16.2° ~ 40.6° | |
| AUTO-IRIS LENS | Yes | |
| AUTO IR-CUT FILTER | Yes | |
| IR LED / EFFECTIVE RANGE | 40 infrared LEDs / ~40m | |
| WEATHER PROOF STANDARD | IP66 | |
| MIN. ILLUMINATION | 0.01 Lux / F1.2 (IR OFF) 0.0 Lux (IR ON), Sense Up | |
| ELECTRONIC SHUTTER | PAL 1/50 ~ 1 / 100,000 sec | NTSC 1/60 ~ 1 / 100,000 sec |
| ELECTRONIC SHUTTER CONTROL | On / Off switchable | |
| BACK LIGHT COMPENSATION | On / Off switchable | |
| NOISE REDUCTION | Auto | |
| S / N RATIO | More than 45dB (AGC off) | |
| WHITE BALANCE | Auto | |
| VIDEO OUTPUT CONNECTOR | 1.0 Vp-p, 75Ω, BNC | |
| AUTO GAIN CONTROL | On / Off switchable | |
| POWER SOURCE | DC 12V / AC 24V | |
| OPERATING TEMPERATURE | -10°C ~ 50°C | |
| NET WEIGHT (G) | 2000 | |
| DIMENSION | 380 (L) x 100 (W) x 230 (H) mm | |

Dimensions

Unit: mm

