



Features

- Resolution: 480(Day) / 550(Night) TVL
- Focal length: 3.4 – 122.4mm
- Min. illumination: 0.01 Lux
- Maximum 432x zoom
- 360° continuous pan
- Auto running
- 24 privacy zones masking
- IP66 weather proof standard

Specifications

MODEL	DM729	DM729IR
PICK UP DEVICE	1/4" Sony CCD	
TOTAL PIXELS	PAL: 752 (H) x 582 (V) NTSC: 768 (H) x 494 (V)	
HORIZONTAL RESOLUTION	Day: 480 TVL Night: 550 TVL	
LENS	3.4 – 122.4mm	
VIEW ANGLE (HORIZONTAL)	1.7° - 57.8°	
MIN. ILLUMINATION	Day: 0.1 Lux /F1.6 Night: 0.01 Lux / F1.6	
ELECTRONIC SHUTTER	PAL: 1/50 - 1/100,000 sec NTSC: 1/60 - 1/100,000 sec	
BACK LIGHT COMPENSATION	On / Off Switchable	
S / N RATIO	More than 50dB (AGC OFF)	
WHITE BALANCE	ATW / AWB / Manual	
VIDEO OUTPUT CONNECTOR	1.0Vp-p (75Ω, Composite)	
AUTO GAIN CONTROL	Yes	
OSD MENU	Yes	
POWER SOURCE	24V AC / 60W (Max)	
IR LED / EFFECTIVE RANGE	Infrared LEDs / 180 – 220m	
OPERATING TEMPERATURE	-40°C ~ 60°C	
WEATHER PROOF STANDARD	IP66	
NET WEIGHT (KG)	9.6	14.5

Dimensions

Unit: mm

